


Switches



LTHS00601*A00

Type	LTHS 60
Number of Poles	1 NO
Mounting Position	Horizontal - vertical
Control Voltage Rating [V _{dc}]	24 ÷ 220
Auxiliary Contact Blocks	Max 4 (1 NO + 1 NC or 2 NO)
Block Type*	SK - SL - LP - RK
Arc chute Material	Ceramic
Contact tips material*	S6

* For details please refer to dedicated technical note

Description

Contactor with single interruption in air, electromagnetic control by full power coil. Single state functioning.

Reference Standard IEC 60077

Electrical Characteristics

Rated Operational Voltage [V _{ac} / V _{dc}]	750
Max Operational Voltage [V _{ac} / V _{dc}]	1000
Rated Insulation Voltage [V]	1000
Conventional Free Air Thermal Current [A] at 75°C	60
DC-Rated Operational Current (τ=15ms) [A]	
750V	60
400V	115
DC-Maximum Breaking Capacity (τ=15ms) [A]	
750V	100
400V	190
AC-Maximum Breaking Capacity (cosφ=0,8; 50Hz) [A]	
750V	110
400V	200
Component Category / Operational Frequency Class	A2 / C3
Short Circuit Withstand Capacity for 5ms [kA]	3
Critical Current Range [A]	< 5 (U > 750V _{dc})
Fault Making Capacity [kA]	1.8
Blow Out Circuit Type	Indirect

Minimum clearances
from metal parts [mm]
X = 80; Y = 80 ; Z = 20

